



41A New London Tpke  
Glastonbury, CT 06033  
Tel 800-558-7080  
sales@tideindustrial.com  
www.tideindustrial.com

## CONVEYOR BELT

<b>Type</b>	<b>White Poli Glide Belt</b>
<b>P/N</b>	1-1120
<b>Description:</b>	U2W Poli-Glide 5S/2U/FS
<b>Color:</b>	White
<b>Nominal OAG:</b>	0.060" +/- .015
<b>Plies:</b>	2 Ply
<b>Fabric:</b>	Polyester
<b>Min Pulley Dia:</b>	0.8"
<b>Top Surface:</b>	Smooth Cover (Satin)
<b>Bottom Surface:</b>	Friction Surface
<b>Compound:</b>	Polyurethane
<b>Work Tension:</b>	35 lbs PIW
<b>Elongation:</b>	Less than 3%
<b>Weight PIW/FT:</b>	.030 lbs
<b>Rec Temp Range:</b>	-22F to 176F
<b>Joining Method:</b>	Lap Splice; Lacing



**Features:** FDA-compliant belt with a thin white urethane top cover and two-ply spun polyester construction, offering easy cleaning, and suitability for small pulleys.

**Uses:** Widely used in bakeries and confectionery operations and in en-robers, cooling lines, dough transfer, cheese manufacturing, and poultry processing.

*\* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*