



41A New London Tpke  
Glastonbury, CT 06033  
Tel 800-558-7080  
sales@tideindustrial.com  
www.tideindustrial.com

## CONVEYOR BELT

**Type** 4-Ply White Nitrile Belt

**P/N** 1-3004

**Description:** White Nitrile OHGR

**Color:** White

**Nominal OAG:** 0.158" +/- .02

**Plies:** 4 Ply

**Fabric:** Cotton/Polyester

**Min Pulley Dia:** 3"

**Top Surface:** 3/64" Smooth Cover

**Bottom Surface:** Friction Surface

**Compound:** NBR

**Work Tension:** 140 lbs PIW

**Elongation:** Less than 2%

**Weight PIW/FT:** .085 lbs

**Rec Temp Range:** 0F to 250F

**Joining Method:** Lap Splice; Lacing



**Features:** Heavy duty white buna belt featuring a special fabric treatment for highest ply adhesion and lowest moisture absorption. This belt has good resistance to oil and grease.

**Uses:** This 4 Ply Nitrile belt can be used in many heavy duty food applications and agriculture. Very popular in the meat and fish industry. FDA Compliant, Oil Resistant, Sliderbed Suitable.

*\* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*