



41A New London Tpke  
Glastonbury, CT 06033  
Tel 800-558-7080  
sales@tideindustrial.com  
www.tideindustrial.com

## CONVEYOR BELT

<b>Type</b>	<b>General Purpose Food</b>
<b>P/N</b>	2-2121X
<b>Description:</b>	W1200 COS Standard
<b>Color:</b>	White
<b>Nominal OAG:</b>	0.135" +/- .020
<b>Plies:</b>	1 Ply
<b>Fabric:</b>	Interwoven Polyester
<b>Min Pulley Dia:</b>	2"
<b>Top Surface:</b>	Smooth PVC
<b>Bottom Surface:</b>	Friction Surface
<b>Compound:</b>	PVC
<b>Work Tension:</b>	120 lbs PIW
<b>Elongation:</b>	Less than 2%
<b>Weight PIW/FT:</b>	.078 lbs.
<b>Temp Range:</b>	0F to 180F
<b>Joining Method:</b>	Finger Splice; Lacing



**Attributes:** Features a smooth PVC cover, tightly interwoven polyester carcass, lies flat and resists stretch. Belt offers vegetable oil resistance but not animal oil resistance.

**Applications:** W1200 COS Standard belt is a general purpose food handling belt. Not recommended for chicken or meat processing. Popular belt for specialty fabrication.

*\* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*