



41A New London Tpke  
Glastonbury, CT 06033  
Tel 800-558-7080  
sales@tideindustrial.com  
www.tideindustrial.com

## CONVEYOR BELT

<b>Type</b>	<b>Diamond Incline Belt</b>
<b>P/N</b>	3-4102
<b>Description:</b>	2 Ply Black Diamond Top
<b>Color:</b>	Black
<b>Nominal OAG:</b>	0.33" +/- 0.02" (recessed 0.15")
<b>Plies:</b>	2 Ply
<b>Fabric:</b>	Polyester
<b>Min Pulley Dia:</b>	2.5"
<b>Top Surface:</b>	Diamond Top Impression
<b>Bottom Surface:</b>	Bare
<b>Compound:</b>	SBR
<b>Work Tension:</b>	120 lbs PIW
<b>Elongation:</b>	Less than 3%
<b>Weight PIW/FT:</b>	.093 lbs
<b>Rec Temp Range:</b>	-20F to 250F
<b>Joining Method:</b>	Use Recessed OAG for Lacing



**Features:** 3-4102 is a high performance belt used for steep inclines. This belt offers a very high coefficient of friction. Rough top impression must be recessed to use lacing.

**Uses:** 2 Ply Black Diamond Top belt used in boxed, bagged and packaged goods applications. Also popular in the airline industry and in post offices. Sliderbed suitable.

*\* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*