



41A New London Tpke
Glastonbury, CT 06033
Tel 800-558-7080
sales@tideindustrial.com
www.tideindustrial.com

CONVEYOR BELT - General Purpose

Type	General Purpose
P/N	4-4002
Description:	150 1/32" x Bare
Color:	Black
Nominal OAG:	0.125" +/- .020
Plies:	2 Ply
Fabric:	Polyester
Min Pulley Dia:	4"
Top Surface:	1/32" SBR Cover
Bottom Surface:	Bare
Compound:	SBR
Work Tension:	150 lbs PIW
Elongation:	Less than 2%
Weight PIW/FT:	.080 lbs.
Rec Temp Range:	-20F to 250F
Joining Method:	Lap Splice; Lacing



Attributes: Bare slider bottom belt featuring an abrasion resistant cover. A good slider belt option in various industries as a light duty general purpose belt.

Applications: Popular in many agricultural applications. Also used in the airline industry, for conveying packaged goods and as a belt for rubber fabrication.

** The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*