

### CONVEYOR BELT

<b>Type</b>	<b>Urethane Recycling Belt</b>
P/N	4-4700
Description:	R1200 Urethane-Novex
Color:	Red
Nominal OAG:	0.187" +/- .020
Plies:	1 Ply
Fabric:	Interwoven Polyester
Min Pulley Dia:	4"
Top Surface:	Urethane
Bottom Surface:	Friction Surface
Compound:	Urethane
Work Tension:	120 lbs PIW
Elongation:	Less than 2%
Weight PIW/FT:	.094 lbs.
Temp Range:	0F to 185F
Joining Method:	Finger Splice; Lacing



**Attributes:** Tough, abrasive, red urethane belt. Interwoven polyester reinforcement with friction surface bottom. Urethane top resists cutting and abrasion from metal, glass and abrasives.

**Applications:** One of our toughest and most abrasion and cut resistant belts useful for metal, glass, aluminum and other abrasive materials. Good for metal stamping, recycling, die cutting and other tough applications.

*\* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*