



41A New London Tpke
Glastonbury, CT 06033
Tel 800-558-7080
sales@tideindustrial.com
www.tideindustrial.com

CONVEYOR BELT

Type	GP Belt 3/16
P/N	5-1511
Description:	150 1/8 x 1/32 STD
Color:	Black
Nominal OAG:	0.236" +/- .030
Plies:	2 Ply
Fabric:	Polyester
Min Pulley Dia:	10"-16" (Tension Dep.)
Top Surface:	1/8" Smooth Cover
Bottom Surface:	1/32" Smooth Cover
Compound:	SBR
Work Tension:	150 lbs PIW
Elongation:	Less than 2%
Weight PIW/FT:	.137 lbs.
Rec Temp Range:	-20F to 200F
Joining Method:	Lap Splice/Lacing



Attributes: 5-1511 features a smooth top and bottom surface and a strong cover. High strength synthetic fabric for longer wear. Low stretch belt.

Applications: Used for moderately abrasive applications. Popular in the sand, gravel and lumber industries. Also great for many flaps, drapes, deflectors, and other wear parts.

** The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*