



41A New London Tpke
Glastonbury, CT 06033
Tel 800-558-7080
sales@tideindustrial.com
www.tideindustrial.com

CONVEYOR BELT

Type	Aggregate
P/N	5-2531
Description:	220 1/8 X 1/16 STD
Color:	Black
Nominal OAG:	0.300" +/- .030
Plies:	2 Ply
Fabric:	Polyester/Nylon
Min Pulley Dia:	12"-18" (Tension Dep.)
Top Surface:	1/8" SBR Cover
Bottom Surface:	1/16" SBR Cover
Compound:	SBR
Work Tension:	220 lbs PIW
Elongation:	Less than 4%
Weight PIW/FT:	.153 lbs.
Rec Temp Range:	-20F to 250F
Joining Method:	Lap Splice; Lacing



Attributes: Features a smooth top and bottom surface with heavy cover and high strength synthetic fabric. Long wearing, low stretch belt. Also mildew and rot resistant.

Applications: Excellent for high abrasion applications. Popular in sand, gravel and rock industries and other heavy industrial applications.

** The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*