



41A New London Tpke
Glastonbury, CT 06033
Tel 800-558-7080
sales@tideindustrial.com
www.tideindustrial.com

CONVEYOR BELT

Type	Recycling Belt
P/N	5-2702
Description:	220 3/16" x Bare MOR
Color:	Black
Nominal OAG:	0.300" +/- .030
Plies:	2 Ply
Fabric:	Polyester/Nylon
Min Pulley Dia:	10"-16" (Tension Dep.)
Top Surface:	3/16" Smooth Cover
Bottom Surface:	Bare
Compound:	MOR
Work Tension:	220 lbs PIW
Elongation:	Less than 2%
Weight PIW/FT:	.165 lbs PIW
Temp Range:	-20F to 200F
Joining Method:	Lap Splice/Lacing



Attributes: Heavy duty, abrasion resistant top cover and bare bottom cover. Can be used on a slider bed and has moderate oil resistance.

Applications: Bare MOR can be used in applications requiring a heavy duty belt on a slider bed. Popular belt for recycling plant applications and the glass industry.

** The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*