



41A New London Tpke
Glastonbury, CT 06033
Tel 800-558-7080
sales@tideindustrial.com
www.tideindustrial.com

CONVEYOR BELT

Type	GP Belt 3/8
P/N	5-2731
Description:	220 3/16 x 1/16 STD
Color:	Black
Nominal OAG:	.360"
Plies:	2 PLY
Fabric:	Polyester/Nylon
Min Pulley Dia:	10"-16" (tension dep.)
Top Surface:	3/16" Smooth Cover
Bottom Surface:	1/16" Smooth Cover
Compound:	SBR
Work Tension:	220 lbs. PIW
Elongation:	Less than 4%
Weight PIW/FT:	.200 lbs.
Temp Range:	-20-250
Joining Method:	Lap Splice/Lacing



Attributes: SBR Belt with high strength, high abrasion, low stretch, mildew resistance. Great heavy duty belt. Also available in thicker 3ply.

Applications: Heavy duty quarry conveyor belt for sand, gravel, rock, ore, limestone and other aggregates. Also used as a heavy duty firewood, split wood, lumber conveyor belt. Popular general purpose belting material for snow plow deflectors, strips, skirting and wear parts.

** The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*