



41A New London Tpke  
Glastonbury, CT 06033  
Tel 800-558-7080  
sales@tideindustrial.com  
www.tideindustrial.com

## CONVEYOR BELT

<b>Type</b>	<b>Bulk Handling Belt</b>
<b>P/N</b>	5-3502
<b>Description:</b>	3 Ply 225 1/8 X Bare MOR
<b>Color:</b>	Black
<b>Nominal OAG:</b>	0.250" +/- .030
<b>Plies:</b>	3 Ply
<b>Fabric:</b>	Polyester/Nylon
<b>Min Pulley Dia:</b>	10"
<b>Top Surface:</b>	Smooth Cover
<b>Bottom Surface:</b>	Bare
<b>Compound:</b>	MOR
<b>Work Tension:</b>	225 lbs PIW
<b>Elongation:</b>	Less than 4%
<b>Weight PIW/FT:</b>	.140 lbs PIW
<b>Rec Temp Range:</b>	-20F to 225F
<b>Joining Method:</b>	Lap Splice/Lacing



**Features:** Durable 3-ply belt with a moderate oil-resistant top cover and low-friction bare bottom, designed for slider-bed and metal pan conveyors with great fastener retention.

**Uses:** Commonly used in recycling and bulk material handling applications where demanding operating conditions are present. Troughable and slider-bed suitable.

*\* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*