



41A New London Tpke  
Glastonbury, CT 06033  
Tel 800-558-7080  
sales@tideindustrial.com  
www.tideindustrial.com

## CONVEYOR BELT

<b>Type</b>	<b>Hot Asphalt</b>
P/N	5-3734
Description:	330 3/16 x 1/16 HA
Color:	Black
Nominal OAG:	0.410" +/- .030
Plies:	3 Ply
Fabric:	Polyester/Nylon
Min Pulley Dia:	12"-18" (Tension Dep.)
Top Surface:	3/16" Smooth Cover
Bottom Surface:	1/16" Smooth Cover
Compound:	NBR
Work Tension:	330 lbs PIW
Elongation:	Less than 4%
Weight PIW/FT:	.217 lbs.
Temp Range:	-20F to 350F
Joining Method:	Lap Splice; Lacing



**Attributes:** High temp and oil resistant NBR, abrasion resistant and retains flexibility at higher temperatures.

**Applications:** Commonly used as hot asphalt belt for carrying hot asphalt and other applications where oil is a factor including oily grains, oil treated coal and sewage treatment.

*\* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*