

41A New London Tpke Glastonbury, CT 06033 Tel 800-558-7080 sales@tideindustrial.com www.tideindustrial.com

## **CONVEYOR BELT**

**Type Wood** P/N 5-3802

Description: 3 Ply 600 3/8 x Bare

**MOR** 

Color: Black

Nominal OAG: .580" +/- .030

Plies: 3 PLY

Fabric: Polyester

Min Pulley Dia: 18-30"

Top Surface: 3/8" Smooth MOR

Bottom Surface: Bare Compound: MOR

Work Tension: 600 lbs PIW Elongation: Less then 2%

Weight PIW/FT: .313 lbs

Temp Range: -20F to 200F

Joining Method: Lap Splice; Lacing



Attributes: This belt features a heavy duty top cover that is abrasion resistant top and a bare bottom cover. Used on a slider bed and has moderately oil resistance.

**Applications:** Useful for many application that need a heavy duty belt on a slider bed. A strong carcass makes it popular in the wood industry.

<sup>\*</sup> The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.