



41A New London Tpke
Glastonbury, CT 06033
Tel 800-558-7080
sales@tideindustrial.com
www.tideindustrial.com

CONVEYOR BELT

Type	HD Aggregate 3 ply
P/N	5-3831
Description:	330 1/4 X 1/16 STD
Color:	Black
Nominal OAG:	0.480" +/- .030
Plies:	3 Ply
Fabric:	Polyester/Nylon
Min Pulley Dia:	12"-18" (Tension Dep.)
Top Surface:	1/4" SBR Cover
Bottom Surface:	1/16" SBR Cover
Compound:	SBR
Work Tension:	330 lbs PIW
Elongation:	Less than 4%
Weight PIW/FT:	.260 lbs.
Rec Temp Range:	-20F to 250F
Joining Method:	Lap Splice; Lacing



Features: Heavy duty 3 PLY aggregate belt. Smooth top and bottom surface. Heavy cover and high strength synthetic fabric provide a long wearing, mildew and rot resistant, low stretch belt.

Uses: Excellent for heavy duty abrasive applications. Used to convey gravel, rock, ore, limestone and many other industrial materials. Also used as an elevator belt.

** The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*