



152 Rockwell Road  
Newington, CT 06111  
Tel 800-558-7080  
sales@tideindustrial.com  
www.tideindustrial.com

## CONVEYOR BELT

<b>Type</b>	<b>Cleated Incline Belt</b>
<b>P/N</b>	5-7531
<b>Description:</b>	220 1/8 x 3/32 Cleated Incline SBR
<b>Color:</b>	Black
<b>Nominal OAG:</b>	0.570" OAG Thk (Recessed 0.325")
<b>Plies:</b>	2 Ply
<b>Fabric:</b>	Polyester
<b>Min Pulley Dia:</b>	10"-16" (Tension Dep.)
<b>Top Surface:</b>	1/4" Chevron Profile
<b>Bottom Surface:</b>	3/32" Cover
<b>Compound:</b>	SBR
<b>Work Tension:</b>	220 lbs PIW
<b>Elongation:</b>	Less than 3%
<b>Weight PIW/FT:</b>	.214 lbs.
<b>Temp Range:</b>	-25F to 250F
<b>Joining Method:</b>	Lap Splice/Lacing



**Attributes:** Staggered pattern 1/4" high x 6" wide chevron profiles. Reinforced SBR popular for heavy duty incline.

**Applications:** Medium and heavy duty cleated incline, bulk conveying, gravel, crushed stone and other aggregate.

*\* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*