



41A New London Tpke
Glastonbury, CT 06033
Tel 800-558-7080
sales@tideindustrial.com
www.tideindustrial.com

CONVEYOR BELT

Type	Cleated Incline Belt
P/N	5-7531
Description:	220 1/8 x 3/32 Cleated Incline SBR
Color:	Black
Nominal OAG:	0.570" OAG Thk (Recessed 0.325")
Plies:	2 Ply
Fabric:	Polyester
Min Pulley Dia:	10"-16" (Tension Dep.)
Top Surface:	1/4" Chevron Profile
Bottom Surface:	3/32" Cover
Compound:	SBR
Work Tension:	220 lbs PIW
Elongation:	Less than 3%
Weight PIW/FT:	.214 lbs.
Temp Range:	-25F to 250F
Joining Method:	Lap Splice/Lacing



Attributes: Staggered pattern 1/4" high x 6" wide chevron profiles. Reinforced SBR popular for heavy duty incline.

Applications: Medium and heavy duty cleated incline, bulk conveying, gravel, crushed stone and other aggregate.

** The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.*