

Lacing Selection Chart



Minimum Pulley Diameter	Belt Thickness																
	Up to .047" or 3/64"	.063" 1/16"	.093" 3/32"	.125" 1/8"	.156" 5/32"	.187" 3/16"	.219" 7/32"	.25" 1/4"	.281" 9/32"	.313" 5/16"	.375" 11/32"	.406" 25/64"	.438" 7/16"	.500" 1/2"	.563" 9/16"	.625" 5/8"	.688" 11/16"
	Up to 1.2mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm	5.6mm	6.4mm	7.1mm	7.9mm	9.0mm	10.0mm	11.1mm	12.7mm	14mm	16mm	17mm
15/16" 24mm	25SP																
	25																
	UCM36SL XSP																
	UCM36SL SP																
	25LP																
1-1/2"; 38mm	00																
	1																
2" 51mm	UCM36 XSP																
	30																
	UCM36 SP																
	36 SP																
	1 XSP																
	30P																
	UX-1 SP																
	RS62																
	MR1																
	UCM36																
	36																
	1 SP																
	7																
	UCM36 LP																
	1																
UX-1																	
UA2																	
U2 SP																	
2SP																	
U2																	
2																	
UA3																	
2-1/2"; 64mm	15																

Chart Continues on Reverse Side

* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.

Minimum Pulley Diameter	Belt Thickness																
	Up to .047" or 3/64"	.063" 1/16"	.093" 3/32"	.125" 1/8"	.156" 5/32"	.187" 3/16"	.219" 7/32"	.25" 1/4"	.281" 9/32"	.313" 5/16"	.375" 11/32"	.406" 25/64"	.438" 7/16"	.500" 1/2"	.563" 9/16"	.625" 5/8"	.688" 11/16"
	Up to 1.2mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm	5.6mm	6.4mm	7.1mm	7.9mm	9.0mm	10.0mm	11.1mm	12.7mm	14mm	16mm	17mm
3" 76mm				U3-1													
				3-1													
				RS125													
				MR2													
				MS25													
				U3-2													
				20													
4" 102mm																	
5" 127mm																	
6" 152mm																	
7" 175mm																	
6"/152mm																	
9"/225mm																	
10"/255mm																	
12"/305mm																	
14"/356mm																	
18" 450mm																	
Minimum Pulley Diameter	Up to .047" or 3/64"	.063" 1/16"	.093" 3/32"	.125" 1/8"	.156" 5/32"	.187" 3/16"	.219" 7/32"	.25" 1/4"	.281" 9/32"	.313" 5/16"	.375" 11/32"	.406" 25/64"	.438" 7/16"	.500" 1/2"	.563" 9/16"	.625" 5/8"	.688" 11/16"
	Up to 1.2mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm	5.6mm	6.4mm	7.1mm	7.9mm	9.0mm	10.0mm	11.1mm	12.7mm	14mm	16mm	17mm

Clipper	Unibar	Alligator	Staple	Bolt Hinged	Rivet Hinged	Bolt Solid Plate	MS	MR
---------	--------	-----------	--------	-------------	--------------	------------------	----	----

* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.