









BELT SPECIFICATION CHART



800-558-7080 • sales@tideindustrial.com









								
P/N	5-2731	5-3731	5-7532	3-1102	5-2731	5-1502	5-3802	2-1121
Type	Sand and Gravel	HD Sand & Gravel	Cleated Incline Gravel and Crushed Stone	Rough Top Firewood	Wood Conveyor Belt	Wood Chips	Heavy Duty Wood	General Purpose PVC
Description	220 3/16 x 1/16 STD	330 3/16 x 1/16 STD	220 1/8 x 3/32 Cleated Incline MOR	2 Ply Rubber R/T	220 3/16 x 1/16 STD	150 1/8 x Bare MOR	3 Ply 600 3/8 x Bare MOR	B1200 COS
Color:	Black	Black	Black	Black	Black	Black	Black	Black
Nominal OAG:	.360"	0.410"	OAG 0.570" (Recessed 0.325")	0.250" +/- .020; Recessed OAG: 0.110" +/- N/A	.360"	0.220" +/- .030	.580" +/- .030	0.135" +/- .015
Plies:	2 Ply	3 Ply	2 Ply	2 Ply	2 Ply	2 PLY	3 PLY	1 Ply
Fabric:	Polyester/Nylon	Polyester/Nylon	Polyester	Polyester	Polyester/Nylon	Polyester/Nylon	Polyester	Interwoven Polyester
Minimum Pulley Dia:	10"-16" (Tension Dep.)	12"-18" (Tension Dep.)	10"-16" (Tension Dep.)	2"	10"-16" (Tension Dep.)	6"	18-30"	3"
Top Surface:	3/16" Smooth Cover	3/16" Smooth Cover	1/4" Chevron Profile	Rubber Hemp Impression	3/16" Smooth Cover	1/8" Smooth Cover	3/8" Smooth MOR	Smooth
Bottom Surface:	1/16" Smooth Cover	1/16" Smooth Cover	3/32" Cover	Bare	1/16" Smooth Cover	Bare	Bare	Brushed
Compound:	SBR	SBR	MOR	SBR	SBR	MOR	MOR	PVC
Work Tension:	220 lbs PIW	330 lbs PIW	220 lbs PIW	150 lbs PIW	220 lbs PIW	150 lbs PIW	600 lbs PIW	120 lbs PIW
Elongation:	Less than 4%	Less than 4%	Less than 3%	Less than 2%	Less than 4%	Less than 2%	Less then 2%	Less than 2%
Weight PIW/FT:	.200 lbs.	.217 lbs.	.214 lbs.	.095 lbs.	.200 lbs.	.110 lbs	.313 lbs	.07 lbs.
Rec Temp Range:	-20F to 250F	-20F to 250F	-20F to 200F	-20F to 250F	-20F to 250F	-20F to 200F	-20F to 200F	0F to 180F
Categories	Sand, Gravel, Rock, Heavy Industrial	Sand, Gravel, Rock, Heavy Industrial	Gravel, Crushed Stone, Bulk Grain, Recycling, Bulk Road Planers.	Incline Belt, Rough Top, Packaged goods, Wood	Sand, Gravel, Rock, Heavy Industrial	Wood, Recycling, Glass, Paper	Wood	General Purpose

* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.

BELT SPECIFICATION CHART



800-558-7080 • sales@tideindustrial.com

								
P/N	2-1151	4-4004	5-2734	5-3734	5-2702	5-7531	4-4700	3-1102
Type	Packaging Belt	Package Slider Top Belt	Hot Asphalt	Hot Asphalt	Recycling Plant Belt	Cleated Incline Recycling Belt	Urethane Recycling Belt	Rough Top Belt
Description	B1500 COS	4 Ply Slider Top	220 3/16 x 1/16 HA	330 3/16 x 1/16 HA	220 3/16" x Bare MOR	220 1/8 x 3/32 Cleated Incline SBR	R1200 Urethane-Novex	2 Ply Rubber R/T
Color:	Black	Tan	Black	Black	Black	Black	Red	Black
Nominal OAG:	0.160" +/- .015	0.120" +/- .020	0.360" +/- .030	0.410" +/- .030	0.300" +/- .030	0.570" OAG Thk (Recessed 0.325")	0.187" +/- .020	0.250" +/- .020; Recessed OAG: 0.110" +/- N/A
Plies:	1 Ply	4 Ply	2 Ply	3 Ply	2 Ply	2 Ply	1 Ply	2 Ply
Fabric:	Interwoven Polyester	Cotton/Polyester	Polyester/Nylon	Polyester/Nylon	Polyester/Nylon	Polyester	Interwoven Polyester	Polyester
Minimum Pulley Dia:	3"	2"	10"-16" (Tension Dep.)	12"-18" (Tension Dep.)	10"-16" (Tension Dep.)	10"-16" (Tension Dep.)	4"	2"
Top Surface:	Smooth PVC	Bare Nylon	3/16" Smooth Cover	3/16" Smooth Cover	3/16" Smooth Cover	1/4" Chevron Profile	Urethane	Rubber Hemp Impression
Bottom Surface:	Brushed	Friction Surface	1/16" Smooth Cover	1/16" Smooth Cover	Bare	3/32" Cover	Friction Surface	Bare
Compound:	PVC	NBR	NBR	NBR	MOR	SBR	Urethane	SBR
Work Tension:	150 lbs PIW	50 lbs PIW	220 lbs PIW	330 lbs PIW	220 lbs PIW	220 lbs PIW	120 lbs PIW	150 lbs PIW
Elongation:	Less than 2%	Less than 2%	Less than 4%	Less than 4%	Less than 2%	Less than 3%	Less than 2%	Less than 2%
Weight PIW/FT:	.090 lbs	.069 lbs	.200 lbs.	.217 lbs.	.165 lbs PIW	.214 lbs.	.094 lbs.	.095 lbs.
Rec Temp Range:	0F to 180F	0F to 250F	-20F to 350F	-20F to 350F	-20F to 200F	-25F to 250F	0F to 185F	-20F to 250F
Categories	Recycling, Package, Baggage, General Purpose	Packaging, Diverting, Slider Top	Hot Asphalt, High Temp, Sewage	Hot Asphalt, High Temp, Sewage	Waste, Recycling, Glass, Slider Bed	Cleated Incline Belt, Bulk Coneying	Recycling, Metal stamping, Manufacturing	Incline Belt, Rough Top, Packaged goods, Wood

* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.

BELT SPECIFICATION CHART



800-558-7080 • sales@tideindustrial.com

P/N	5-7531	3-1620	5-8642	1-2002	1-2350	2-2121X	4-3005	4-1111
Type	Cleated Incline Belt	Cleated Z Belt	Mini Bucket Cleated Belt	Food Grade Belt	Meat Packing	General Purpose Food	Feed and Grain	Potato and Vegetable
Description	220 1/8 x 3/32 Cleated Incline SBR	P2 B220 Z-Cleat	2 Ply 150 Mini-Bite 1/32" x Bare	2 PLY OHGR	RAV2 W100 Meat Cleat	W1200 COS Standard	5 Ply Tan Transmission HD	PC2 B150 CBS
Color:	Black	Black	Black	White	White	White	Tan	Black
Nominal OAG:	0.570" OAG Thk (Recessed 0.325")	0.450" +/- .020	0.290" +/- .030	.090" +/- .015	0.250" +/- .020	0.135" +/- .020	0.270" +/- .020	0.160" +/- .015
Plies:	2 Ply	2 Ply	2 Ply	2 PLY	2 PLY	1 Ply	5 PLY	2 PLY
Fabric:	Polyester	Interwoven Polyester	Polyester	Polyester	Polyester	Interwoven Polyester	Cotton	Polyester
Minimum Pulley Dia:	10"-16" (Tension Dep.)	8"	8"	2"	1-1/2"	2"	8"	2-1/2"
Top Surface:	1/4" Chevron Profile	1/4" Z Profile	Mini-Bucket Profile	NBR Cover	Meat Cleat Impression	Smooth PVC	Friction Surface	Smooth Satin
Bottom Surface:	3/32" Cover	Skim	Bare	Friction Surface	Friction Surface	Friction Surface	Friction Surface	Smooth Satin
Compound:	SBR	PVC	SBR	NBR	RAV	PVC	SBR	PVC
Work Tension:	220 lbs PIW	220 lbs PIW	150 lbs PIW	70 lbs PIW	100 lbs PIW	120 lbs PIW	175 lbs PIW	150 lbs PIW
Elongation:	Less than 3%	Less than 2%	Less than 2%	Less than 2%	Less than 2%	Less than 2%	Less than 3%	Less than 2%
Weight PIW/FT:	.214 lbs.	.172 lbs.	.085 lbs.	.054 lbs	.092 lbs	.078 lbs.	.131 lbs	0.091 lbs
Rec Temp Range:	-25F to 250F	20F to 180F	-25F to 250F	0 to 250 F	20F to 180F	0F to 180F	-40F to 250F	-20F to 180F
Categories	Cleated Incline Belt	Cleated, Recycling, Wood, Agriculture	Cleated Incline Belt, Sand, Gravel, Recycling, GP	Food Grade Belt, Meat, Fish	Meat Packing, Vegetable, Bakery	General Purpose Food	Agriculture, Feed, Grain	Potatoes, Fruits, Vegetables, Fertilizers

* The data contained here are approximate values dependent on belt dimensions, application and environment and is for reference only. It is believed to be reliable, but no representations, guarantees or warranties of any kind are made to its accuracy or suitability for any particular purpose. It is recommended that users conduct their own evaluations for the intended application.